

EN

- Hand-made art glass products are designed for installation in interiors only.
- Glass insertos are separate decorative elements, whose graphic patterns are not continuous.
- The glass strip is adorned with a unique, hand-made pattern.
- Rounded and wavy edges result from glass structure and are intended.
- Patterns on glass decorative elements may be slightly repositioned, up to 2 mm.
- Color changes in various light conditions (illumination angle) and minor structural differences are intended.
- Installation without grout is not recommended, especially when combining glass decorative elements with rectified tiles.
- Do not use coarse grout. When applying grout, protect the surface of decorative elements, e.g. with adhesive tape.
- Do not use aggressive or coarse cleaning liquids and agents that may damage the surface of decorative elements.
- Protect the face and back surfaces of glass decorative elements against damage.
- Place pallets on hard, even and dry surface. Do not stack.

Caution: Special ceramics - art glass.

INSTALL GOODS USING CERAMIC TILES ADHESIVES.

Special hand-made ceramic products are designed for installation in interiors only. Prior to installation, check the quality of installation surface and dimensions by comparing items from different boxes. CHECK FOR MATCHING DESIGNATIONS ON BOXES: COLOR SHADE, SIZE.

COMPLAINTS WITH REGARD TO CALIBER AND COLOR SHADES WILL NOT BE ACCEPTED ONCE THE TILES ARE INSTALLED.

CAUTION GLASS

Product characteristics		Value declared by the manufacturer						Source of entry
		Length of l item [cm]						
		l≤5	5<l≤7	7<l≤20	20<l≤40	40<l≤60	l>60	
Length and width		±2,0[%]	±1,5[%]	±0,5[%]	±0,3[%]	±0,2[%]	±0,15[%]	EN ISO 10545-2
Thickness	≤8mm	+5[%] -10[%]	+5[%] -10[%]	+5[%] -10[%]	+5[%] -10[%]	+5[%] -10[%]	+5[%] -10[%]	EN ISO 10545-2
	≥8mm	+3[%] -8[%]	+3[%] -8[%]	+3[%] -8[%]	+3[%] -8[%]	+3[%] -8[%]	+3[%] -8[%]	EN ISO 10545-2
Side curvature		±2,0[%]	±1,5[%]	±0,5[%]	±0,3[%]	±0,2[%]	±0,15[%]	EN ISO 10545-2
Right angle surface flatness	Central curvature	+2,0[%]	+1,5[%]	+0,5[%]	+0,3[%]	+0,2[%]	+0,15[%]	EN ISO 10545-2
Surface quality		At least 95% of tiles and/or glass decorative elements should not have visible defects.						EN ISO 10545-2
Water absorbency		E≤0,5%						EN ISO 10545-3
Yield strength		≥1300 [N]						EN ISO 10545-4
Bending resistance		≥35 [N/mm ²]						EN ISO 10545-4
Hair cracking resistance		Resistant						EN ISO 10545-11
Resistance to household chemicals		GB minimum						EN ISO 10545-13
Stain resistance		Class 3 minimum						EN ISO 10545-14

V1/2013.05.01

